

See "Rigid Material Application Notes" and manufacturer's website for specific, detailed guidelines and instructions.

GENERAL INFORMATION

MATERIAL DESCRIPTION

Sintra® has been the industry's leading PVC board for more than 20 years. It is a lightweight yet rigid and durable board comprised of moderately expanded closed-cell polyvinyl chloride (PVC) in a homogenous sheet with a low-gloss matte finish. It is easily formed into just about any shape imaginable using wood and foam board fabrication techniques; Heat formable and chemical resistant; Superior dent and scratch resistance.

RECOMMENDED APPLICATIONS

- P-O-P Displays medium-term application life
- Exhibits & Kiosks medium-term application life
- Framing long-term application life
- Framing - Archival long-term application life
- Signage - Interior medium-term application life
- Signage - Exterior medium-term application life

CAUTIONS

1. Be specific when ordering material as there are many similar materials and finishes, yet performance and results will vary significantly, even among like materials.
2. Be sure to measure dimensions of material prior to printing as they are not always consistent.
3. The following may cause adverse effects on ink adhesion and durability:
 - Failure to acclimate material to ambient conditions for at least 24 hours.
 - Failure to print under recommended ambient conditions.
 - Neglecting to properly clean the print surfaces. This will allow debris to be visible after printing. Ensure that 99% isopropyl alcohol is used for cleaning.
 - Using thinners or soaps which may leave a film residue which can affect adhesion. Additionally, cleaners containing silicone can interfere with adhesion and are not recommended.
4. Elevated UV exposure can affect PVCs printed with UV ink, causing brittleness in the printed areas of the sheet.
5. Ink adhesion increases at higher pass modes (8 Pass > 4 Pass > 2 Pass).

WARNING: Be sure that material is completely flat. Bent edges may cause damage to printheads and/or other hardware. Tape down edges as necessary. Leaning may cause warping.

PERFORMANCE TESTING RESULTS

See "Material Performance Testing Process" document for process explanation and test conditions.

ADHESION TESTING

Tape Test: Level 5, Excellent
Cross-Hatch Test: Level 0, Very Poor

ABRASION RESISTANCE

Level 5, Excellent

CHEMICAL RESISTANCE

Level 5, Excellent

OUTDOOR DURABILITY

GerberCAT inks are outdoor durable for up to 3 years. Consult material manufacturer for durability of substrate. Testing of application in intended environment is advised.

MATERIAL HANDLING RECOMMENDATIONS

STORAGE

1. Flat, horizontally only. Leaning will allow warping.
2. Cool, dry, clean area with stable temperature.

SURFACE PREPARATION

1. Print surface should be free and clear of any surface contaminants (i.e. oils, dust, fingerprints, etc.) prior to printing.
2. Clean with 99% isopropyl alcohol, using a non-colored cloth. Best results have been obtained when applying the alcohol to the wiping cloth rather than directly to the material.
3. Any surface scratches on the substrate will have a tendency to telegraph through the graphic. In order to remove small scratches or dents, rapidly fan a heat gun over the affected area. Care must be taken not to leave the hot air in one place for too long, as the surface can be deformed.

POST-PRINT

Ink cures enough to be touched immediately without adverse effect. Full cure occurs between 15 minutes and 24 hours dependent upon material and ambient conditions. Cutting, routing, or any additional undertakings should run flawlessly. If any flaking or cracking occurs, allow to sit 24 hours for full cure. Best cutting results are obtained with carbide-tipped router bits.

See manufacturer's website for more information.

TESTED PRINT CONDITIONS

AMBIENT TEMPERATURE

70°F (21°C)

AMBIENT HUMIDITY

40%, non-condensing


PRINTER RESOLUTION

360 dpi

PRINT MODE

4 Pass, Unidirectional

COLOR GAMUT



COLOR MANAGEMENT

RECOMMENDED RENDERING INTENTS

CMYK Vector: Relative colorimetric
CMYK Image: Perceptual
RGB Vector: Relative colorimetric
RGB Image: Perceptual

MATERIAL PROFILES

The recommended profile can be downloaded from the corresponding materials page on the gspinc.com/applications webpage.

CAUTION: Failure to manage color settings consistently throughout the entire workflow, from image generation through final print, will result in guesswork and unpredictable and potentially unfavorable end results.

