



Gerber UVGuard™ 9 Overlamine manufactured by 3M

DESCRIPTION.....	1
INTENDED APPLICATIONS	1
PERFORMANCE LIFE IMPROVEMENT	1
SHELF LIFE AND STORAGE	2
MAINTENANCE	2
APPLICATION TECHNIQUES	2
PHYSICAL PROPERTIES.....	2
RELATED LITERATURE.....	2
CONTACT INFORMATION	2

DESCRIPTION

Gerber UVGuard 9 is a glossy, 2-mil, clear, PVC laminating film with a graphic protection system top coat designed to further expand the resistance to weathering of graphics printed (or cut) on Gerber Series 220, 225 or 280i, all manufactured by 3M. These films can all be used with the GERBER EDGE®, GERBER EDGE 2®, and GERBER EDGE FX™ thermal transfer printing systems, in conjunction with GerberColor™ Foils.

Gerber UVGuard 9 has the highest protection from UV fade.

INTENDED APPLICATIONS

Graphics that are applied to non-vertical or horizontal flat surfaces or markings installed in areas that experience maximum sunny days will benefit most from the application of Gerber UVGuard 9. Graphics that have been laminated with Gerber UVGuard 9 can be applied to flat surfaces. Gerber UVGuard 9 is not recommended for application to compound surfaces.

In addition, application to corrugated or corrugated with riveted surfaces is not recommended. Application to flat surfaces with rivets must be done on a test and approval basis only.

For information on further protecting graphics from petrochemical or abrasive exposure, refer to Gerber Guard™ and Abrasion Guard™ SPF product bulletins.

PERFORMANCE LIFE IMPROVEMENT

The expected performance life of graphics printed with GerberColor Spot*, GerberColor Process Pro™ CMYK, or GerberColor Transparent Foils on Gerber Series 220, 225, or 280i (all manufactured by 3M), overlaminated with Gerber UVGuard 9, will be improved to up to nine years.

*The performance life of GerberColor Spot Pink (GCS-643) will not be affected by Gerber UVGuard 9. This performance life improvement statement is based upon laboratory tests, exposure tests, and field tests believed to be reliable. Actual performance can be affected by substrate environmental conditions, and maintenance of markings.

SHELF LIFE AND STORAGE

Apply film within one year of receipt. Gerber UVGuard 9 should be stored in a clean area free from excessive moisture and sunlight. Storage temperature is 40° to 100°F (4° to 38°C).

MAINTENANCE

Clean the face of Gerber UVGuard 9 with a mild, non-abrasive soap with a soft cloth or sponge. The cleaner must have a pH value between 3.0 and 11.0. Avoid soaps containing grit, abrasives, strong solvents or alcohol.

APPLICATION TECHNIQUES

Note: Use the minimum amount of pressure needed and unwind tension to obtain good results. This helps reduce the chance of the overlamine tunneling as it is applied.

The following application procedure is recommended for applying Gerber UVGuard 9 to your printed graphic:

1. Print your graphics with Gerber Series 220 or 225.
2. Take the printed 220 or 225 out of the printer.
3. Using a cold roll laminator (preferred), or by hand (use application tape), apply Gerber UVGuard 9 over the printed graphic. Use care to ensure that the punch holes of the 220 or 225 are not obstructed by the laminate.
4. Load laminated graphic into the plotter and line up the cut registration mark using the "bomb sight".
5. Increase your tool force setting on your plotter before cutting the laminated graphic. The optimal cut will penetrate through the laminate and base film without cutting through the liner.
6. Weed graphic as you normally would.

PHYSICAL PROPERTIES

Thickness	2 mil
Film Color	Clear
Adhesive	Permanent
Adhesive Color	Clear
Liner	Kraft paper
Application Temperature	50°F to 100°F (10°C to 37°C)
Operating Temperature	-65°F to 225°F (-54°C to 107°C)

RELATED LITERATURE

Refer to Product Bulletins of relevant foils and materials for product-specific handling, production, and finishing information.

CONTACT INFORMATION

For help with questions concerning Gerber products, please call your distributor or Gerber Customer Service at 1-800-222-7446 or (860) 644-1551. Visit us on the Internet at www.gspinc.com to learn more about our many other foils, materials and equipment.

When sold by Gerber, use only the corresponding Gerber Product Bulletin to determine product details, including but not limited to appropriate uses, warranty and processing.

EDGE, GERBER EDGE, GERBER EDGE 2, Gerber Scientific Products, GerberCal, GerberGraphics, GRAPHIX ADVANTAGE, GSP, and Images on Vinyl are Registered Trademarks of Gerber Technology.

Abrasion Guard, ColorSet, EDGE Positive, EDGE READY, Gerber AutoMag, GERBER EDGE FX, Gerber FastFacts, Gerber Guard, Gerber HoloGraphix, Gerber ImageCal, Gerber ImageCast, Gerber InstaChange, Gerber OMEGA, Gerber PermaGrip, Gerber PlastiGraphix, Gerber QUANTUM, Gerber Stardust, Gerber StrikeGuard, Gerber Tone, Gerber UVGuard, GerberCal, GerberColor, GerberColor Spectratone, GerberGauge, GerberGlow, GerberMag, GerberMask, GerberVision, GS 15, GS15plus, GSP Plot, GSxplus, GSx, ImagePerfect, IMAGE READY, LexEdge, Matched Technology System, MTS, ODYSSEY, OMEGA, Process Pro, SpectraShade, and SpectraTint are Trademarks of Gerber Technology.

3M is a trademark of 3M Company.

©2015 Gerber Technology. All Right Reserved

Category: Materials

FastFact #: N/A

Supplied by: Aftermarkets

Last Modified: 09/03/15